

Eaton 9E-IN

03 kVA 1x1 (Inbuilt Battery) UPS

Manufacturer's declaration in accordance with IEC 62040-3



Value Proposition:

High Performance

- True Online Double Conversion
- True Input PF 0.99
- True output PF 0.9
- Output THDv 2%
- Higher Power Density
- Higher Efficiency upto 98% in ECO Mode
- Support Critical Virtualization

High Reliability and Adaptability

- Wide Input Voltage Range 110 to 300 Vac
- Inbuilt Hardware Current Limit Technology.
- Upgraded Phase Lock Algorithm
- Inbuilt Over-voltage Cut-off Device
- Inbuilt Over Temperature Protection.
- Upto 50 Degree Celsius operation @50% Load (Specific to XL Model)
- Better Overload Protection upto 105% Constant

High Flexibility and Availability

- Adjustable Charging Current 0 to 1.5 Amps
- Better Short Ckt Handling Capacity.
- Auto Fault Recovery.
- Conformal Coated Boards.
- More Accessories.

Major Application

- Networking/Server/Storage.
- Wiring Closets.
- Security and Surveillance System.
- Industrial Automation Control.
- Laboratory Equipment.
- ATM/Telecom/Railway Signalling.



Powering Business Worldwide

Technical Specification of Eaton 9E-IN 3 kVA-Inbuilt Battery.

Model Name	Eaton 9E-IN 3000
Catalog number	E9E3K-IN
Plant Part Number	9103-83928XT1
UPC Code	743172091864
INPUT Characteristics	
Acceptable Input Voltage	100VAC-300VAC
Phase	Single phase with ground
Transfer Voltage Range (low load)	100VAC-300VAC (40% load)
Transfer Voltage Range (100% load)	176VAC-300VAC
-Line low loss	160VAC/100VAC ($\pm 3\%$)
-Line low comeback	165VAC/105VAC ($\pm 3\%$)
-Line high loss	300VAC ($\pm 3\%$)
-Line high comeback	290VAC ($\pm 3\%$)
Nominal input current (r.m.s) @ 230V input and battery fully recharged	13.2A
Inrush Current Limit	8*I _{rms}
THDi	5 % typical, 7% Max with R full load @ 230v input
Input Power Factor	≥ 0.99 (R FULL LOAD) @ 230V input
Input Frequency Range	45-55Hz / 54-66Hz
Input protection	Breaker
OVCD	Withstand 440Vac, 24Hours
Generator Set	2.2 x UPS Rating Power
OUTPUT Characteristics	
Output Power(VA) max	3000
Output Power(W) max	2700
Output Power Factor	0.9
Output Waveform	Pure sine wave
Output nominal voltage	220VAC/230VAC/240VAC
Output Voltage Variation	$\pm 1\%$
Output Transient recovery	100ms (IEC 62040-3 Non-linear load)
Output Voltage distortion	< 2% THD, linear load @ Line mode < 2% THD, linear load @ battery mode, battery voltage 12V / per battery
	< 6% THD, linear load @ Line mode < 6% THD, linear load @ battery mode, battery voltage 12V / per battery
Output Frequency in inverter mode Synchronization range	45-55Hz / 54-66Hz
Output Frequency Slew rate	1 Hz/s
Output Frequency in Battery mode	(50/60 \pm 0.05) Hz
Transfer time Inverter Mode to Battery Mode.	0ms
Transfer Time Inverter Mode to Bypass Mode.	4ms
Line mode efficiency @ full load with battery fully charged	>91%
ECO mode efficiency @ full load with battery fully charged	>98%
Battery mode efficiency @ full load 12Vdc/Battery	>88.1%
Overload Capability (Line mode)	100%~105% :Constant
	105%~130% :60s
	130%~150% :10s
	>150% :300ms
Overload Capability (Battery mode)	100%~105% :Constant
	105%~130% :10s
	130%~150% :1s
	>150% :300ms
	>105% and V _{bat} <10.5V: 300ms

BATTERY Characteristics	
DC Voltage	72VDC
Battery-Low Voltage(full load)	63VDC, 10.5V/pcs
Battery shutdown voltage @ 0 ~ 20% Load (for long run model) / 0~ 30% (for standard model)	64.2VDC, 10.7V/pcs
Battery shutdown voltage @ 20 ~ 70% Load (for long run model) / 30%~70% load (for standard model)	61.2VDC, 10.2V/pcs
Battery shutdown voltage @ > 70% Load	57VDC, 9.5V/pcs
Charger Current	1.5A
Leakage current	< 150uA
FEATURES	
ECO Mode	YES
EPO Function	NA
Battery Capacity Calculation	YES
Fan Speed Control	YES
Frequency Converter Mode(CVCF)	YES, 60% load
INTERFACE	
RS232	Yes
USB	NA
COM Slot	YES
NMC card	Optional
AS400 card(Dry contact card)	Optional
Modbus card	Optional
Input connection	Input terminal block
Outlet socket	4 x IEC 10A outlets, 1 terminal block
MECHANICAL Standards	
WxHxD (mm)	190 x 327 x 399
Net Weight	22.7Kg
Operating Temperature Range	0°C ~ 40 °C
Relative Humidity	0 ~ 95% (No condensing)
Audible Noise	<41dB at front 1m @ typical load
Regulations and Standards	
-ESD	IEC 61000-4-2 Level 3
-RS	IEC 61000-4-3 Level 3
-EFT	IEC 61000-4-4 Level 4
-Surge	IEC 61000-4-5 Level 4
-Safety	BIS
-Transportation	ISTA 2A
-Protection	IP20 (static)
ACCESSORIES	
User manual	Yes
External battery power cord	NA

EMC Standards	
Conduction	Class 2 Ref Std: IEC 62040-2:2005
Radiation	Class 2 Ref Std IEC 62040-2:2005
Low frequency conducted disturbances	Criteria A Ref Std : IEC61000-2-2:2002
Harmonic current	Class A Ref Std :IEC 61000-3-2:2014
ESD	Criteria B, Level 3 Ref Std : IEC 61000-4-2:2008
RS	Criteria A, Level 3 Ref Std IEC 61000-4-3:2006+AMD1:2007+AMD2:2010 CSV
EFT	Criteria B ,Level 4 Ref Std :IEC 61000-4-4:2012
Surge	Criteria B, DM Level 3: 2KV, CM Level 4: 4KV Ref Std : IEC 61000-4-5:2014
C/S	Criteria A, level 3 Ref Std : IEC61000-4-6:2013
M/S	Criteria B, level 4 Ref Std : IEC61000-4-8:2009
Voltage Dips, short interruptions and voltage variations	Criteria B ,Level 4 Ref Std : IEC61000-4-11: 2004
Certificate	
BIS	YES
CE	YES



Powering Business Worldwide

Americas Region

1000 Eaton Boulevard
Cleveland, Ohio 44122, USA

India Head Office

Eaton Power Quality Pvt. Ltd.
2, EVR Street, Sedarpet
Industrial Estate
Pondicherry-605111
Tel: +91 413 2672000

Sales and Service

Toll Free Hotline:
1800 425 5758

Offices Across India

DELHI

Unit A1 & B1, 3rd Floor, TDI Centre
Plot No. 7, Jasola, New Delhi-110025
Tel: +91 11 45851800

MUMBAI

EL Floor, VITS Luxury, Business Hotel
Andheri Kurla Road, Andheri (East)
Mumbai-400059
Tel: +91 22 40053817, Fax: +91 22 40053810

CHENNAI

No. 36, Nehru Street
Off. Old Mahabalipuram Road
Sholinganallur, Chennai-600119
Tel: +91 44 2532 0249

BANGALORE

Unit No. 501, 4th Floor, Prestige Atrium
Central Street, Bangalore-560001
Tel: +91 80 49012200, Fax: +91 80 49012239

HYDERABAD

Ground & First Floor, 8-3-1110/B/2
Plot No. 104, Keshav Nagar Colony
Srinagar Colony Post, Hyderabad-500073
Tel: +91 40 40189601

KOLKATA

Room No. 203, 2nd Floor
Matrix Tower, DN 24, Sector-V
Salt Lake City, Kolkata-700091
Tel: +91 33 40040991/92/93