

# Eaton 9E-IN

## 01 kVA 1x1 (XL Model) UPS

Manufacturer's declaration in accordance with IEC 62040-3



### Value Proposition:

#### High Performance

- True Online Double Conversion
- True Input PF 0.99
- True output PF 0.8
- Output THDv 2%
- Higher Power Density
- Higher Efficiency upto 98% in ECO Mode
- Support Critical Virtualization

#### High Reliability and Adaptability

- Wide Input Voltage Range 110 to 300 Vac
- Inbuilt Hardware Current Limit Technology.
- Upgraded Phase Lock Algorithm
- Inbuilt Over-voltage Cut-off Device
- Inbuilt Over Temperature Protection.
- Upto 50 Degree Celsius operation @50% Load (Specific to XL Model)
- Better Overload Protection upto 105% Constant

#### High Flexibility and Availability

- Adjustable Charging Current 2A-10 Amps
- Better Short Ckt Handling Capacity.
- Auto Fault Recovery.
- Conformal Coated Boards.
- More Accessories.

#### Major Application

- Networking/Server/Storage.
- Wiring Closets.
- Security and Surveillance System.
- Industrial Automation Control.
- Laboratory Equipment.
- ATM/Telecom/Railway Signalling.



Powering Business Worldwide

## Technical Specification of Eaton 9E-IN 1 kVA-XL

Model Name	Eaton 9E-IN 1000XL
Catalog number	E9E1KXL-IN
Plant Part Number	9103-53820XT1
UPC Code	743172091802
<b>INPUT Characteristics</b>	
Acceptable Input Voltage	100VAC-300VAC
Phase	Single phase with ground
Transfer Voltage Range (low load)	100VAC-300VAC (50% load)
Transfer Voltage Range (100% load)	160VAC-300VAC
-Line low loss	160VAC/100VAC ( $\pm 3\%$ )
-Line low comeback	170VAC/110VAC ( $\pm 3\%$ )
-Line high loss	300VAC ( $\pm 3\%$ )
-Line high comeback	290VAC ( $\pm 3\%$ )
Nominal input current (r.m.s) @ 230V input and battery fully recharged	3.95A
Inrush Current Limit	8*Irms
THDi	<9% with R full load @ 230V input
Input Power Factor	$\geq 0.99$ (R FULL LOAD) @ 230V input
Input Frequency Range	45-55Hz / 54-66Hz
Input protection	Breaker
OVCD	Withstand 440Vac, 24Hours
Generator Set	2.2 x UPS Rating Power
<b>OUTPUT Characteristics</b>	
Output Power(VA) max	1000
Output Power(W) max	800
Output Power Factor	0.8
Output Waveform	Pure sine wave
Output nominal voltage	200VAC/208VAC/220VAC/230VAC/240VAC
Output Voltage Variation	$\pm 1\%$
Output Transient recovery	100ms (IEC 62040-3 Non-linear load)
Output Voltage distortion	< 3% THD, linear load@Line mode < 3% THD, linear load @ battery mode, battery voltage 12V / per battery < 7% THD, non-linear load@line mode < 7% THD, non-linear load @ battery mode, battery voltage 12V / per battery
Output Frequency in inverter mode Synchronization range	45-55Hz / 54-66Hz
Output Frequency Slew rate	1 Hz/s
Output Frequency in Battery mode	(50/60 $\pm$ 0.05) Hz
Transfer time Inverter Mode to Battery Mode.	0ms
Transfer Time Inverter Mode to Bypass Mode.	4ms
Line mode efficiency @ full load with battery fully charged	>88%
ECO mode efficiency @ full load with battery fully charged	>97.35%
Battery mode efficiency @ full load 12Vdc/Battery	>85%
Overload Capability (Line mode)	100%~105% :Constant 105%~130% :60s 130%~150% :10s >150% :300ms
Overload Capability (Battery mode)	100%~105% :Constant 105%~130% :10s 130%~150% :1s >150% :300ms >105% and Vbat<10.5V: 300ms

BATTERY Characteristics	
DC Voltage	36VDC
Battery-Low Voltage(full load)	33.6VDC, 11.2V/pcs
Battery shutdown voltage @ 0 ~ 20% Load (for long run model) / 0~ 30% (for standard model)	33VDC, 11V/pcs
Battery shutdown voltage @ 20 ~ 70% Load (for long run model) / 30%~70% load (for standard model)	31.5VDC, 10.5/pcs
Battery shutdown voltage @ > 70% Load	30VDC, 10V/pcs
Charger Current	10A (2/4/6/8/10A adjustable)
Leakage current	<300uA
FEATURES	
ECO Mode	YES
EPO Function	NA
Battery Capacity Calculation	YES
Fan Speed Control	YES
Frequency Converter Mode(CVCF)	YES, 60% load
INTERFACE	
RS232	Yes
USB	NA
COM Slot	YES
NMC card	Optional
AS400 card(Dry contact card)	Optional
Modbus card	Optional
Input connection	input powercord 6A
Outlet socket	3 x IEC 10A outlets
MECHANICAL	
WxHxD (mm)	102X228X346
Net Weight	3.8Kg
Operating Temperature Range	0°C ~ 40 °C
Relative Humidity	0 ~ 95% (No condensing)
Audible Noise	≤45dB at front 1m
Regulations and Standards	
-ESD	IEC 61000-4-2 Level 3
-RS	IEC 61000-4-3 Level 3
-EFT	IEC 61000-4-4 Level 4
-Surge	IEC 61000-4-5 Level 4
-Safety	BIS
-Transportation	ISTA 2A
-Protection	IP20 (static)
ACCESSORIES	
User manual	Yes
External battery power cord	NA

EMC Characteristics	
Conduction	NA
Radiation	NA
Low frequency conducted disturbances	Criteria A Ref Std : IEC61000-2-2:2002
Harmonic current	Class A Ref Std :IEC 61000-3-2:2014
ESD	Criteria B, Level 3 Ref Std : IEC 61000-4-2:2008
RS	Criteria A, Level 3 Ref Std IEC 61000-4-3:2006+AMD1:2007+AMD2:2010 CSV
EFT	Criteria B ,Level 4 Ref Std :IEC 61000-4-4:2012
Surge	Criteria B, DM Level 3: 2KV, CM Level 4: 4KV Ref Std : IEC 61000-4-5:2014
C/S	Criteria A, level 3 Ref Std : IEC61000-4-6:2013
M/S	Criteria B, level 4 Ref Std : IEC61000-4-8:2009
Voltage Dips, short interruptions and voltage variations	Criteria B ,Level 4 Ref Std : IEC61000-4-11: 2004
Certificate	
BIS	YES
CE	NA



Powering Business Worldwide

#### Americas Region

1000 Eaton Boulevard  
Cleveland, Ohio 44122, USA

#### India Head Office

Eaton Power Quality Pvt. Ltd.  
2, EVR Street, Sedarpet  
Industrial Estate  
Pondicherry-605111  
Tel: +91 413 2672000

#### Sales and Service

**Toll Free Hotline:**  
1800 425 5758

#### Offices Across India

##### DELHI

Unit A1 & B1, 3rd Floor, TDI Centre  
Plot No. 7, Jasola, New Delhi-110025  
Tel: +91 11 45851800

##### MUMBAI

EL Floor, VITS Luxury, Business Hotel  
Andheri Kurla Road, Andheri (East)  
Mumbai-400059  
Tel: +91 22 40053817, Fax: +91 22 40053810

##### CHENNAI

No. 36, Nehru Street  
Off. Old Mahabalipuram Road  
Sholinganallur, Chennai-600119  
Tel: +91 44 2532 0249

##### BANGALORE

Unit No. 501, 4th Floor, Prestige Atrium  
Central Street, Bangalore-560001  
Tel: +91 80 49012200, Fax: +91 80 49012239

##### HYDERABAD

Ground & First Floor, 8-3-1110/B/2  
Plot No. 104, Keshav Nagar Colony  
Srinagar Colony Post, Hyderabad-500073  
Tel: +91 40 40189601

##### KOLKATA

Room No. 203, 2nd Floor  
Matrix Tower, DN 24, Sector-V  
Salt Lake City, Kolkata-700091  
Tel: +91 33 40040991/92/93